

Collier Group

Collblock

Scotland's only carbon neutral concrete block producer

PRODUCT DATA

Standard and paint grade blocks produced and tested to BS EN771-3 2011 available below 20 kg at 3% moisture content with dimensions of:

440 mm length x 100 mm width x 215 mm height
290 mm length x 140 mm width x 215 mm height

Also available are dimensions of:

440 mm length x 140 mm width x 140 mm height
and spacer bricks to alleviate the need to cut blocks.

Compressive Strength

Concrete blocks are available in strengths from 7.3 N/mm² to 22.5 N/mm²

Drying Shrinkage

Drying shrinkage is below 0.06 %, and all blocks are non-combustible and frost resistant.

Product Application

Blocks can be used below DPC, external and internal walls, separation, sound reduction & reinforced walls.

Quality Control

A BSI cat 2 quality control system is being operated from our internal laboratory.

More in depth product analysis & information is available at customer's request.

COLLIER HAULAGE Ltd.

Reg. No. SC300061

TEL: 01383 510329

www.collierhaulage.co.uk

GOATHILL QUARRY, EASTER BUCHLYVIE,

COLLIER QUARRYING AND RECYCLING Ltd.

Reg. No. SC212435

FAX: 01383 610331

email: info@collierhaulage.co.uk

COWDENBEATH, FIFE KY4 8ES